

Clack Corporation

WS2

WATER SPECIALIST 2" CONTROL VALVE

shown with optional bypass valve



- **2" top mount or side mount control valve suited for commercial and industrial applications**
- **Lead free brass valve body and optional bypass valve**
- **Meter standard with all valves**
- **Service flow rate 125 gpm (473 lpm), Backwash flow rate 125 gpm (473 lpm)**
- **Solid state microprocessor with easy access front removable POD**
- **Front panel display for Time of Day, Current Flow Rate, Totalizer and Volume/Days until Regeneration**
- **Four methods to initiate the down flow regeneration; meter delayed, meter immediate, time clock delayed, or pressure differential**
- **Fully programmable regeneration cycle sequences (maximum 9)**
- **Fully programmable regeneration cycle times**
- **Treated water regenerant refill**
- **Days override feature; 1-28 days available**
- **Capacitor back-up with up to 24 hour power carry over**
- **24-volt output AC adapter provides safe and easy installation**
- **Reliable and proven DC drive**

Water Specialist 2" Control Specifications

Inlet/Outlet (1)	2" FPT or 2.5" Victaulic
Cycles	up to 9
Valve Material	Lead free brass
Regeneration	downflow

FLOW RATES

Service @15 psi drop (includes meter)	125 gpm (473 lpm)
Backwash @ 25 psi drop.....	125 gpm (473 lpm)
Cv Service.....	32.3
Cv Backwash.....	25.0

OPERATING PRESSURES

Minimum/Maximum	20 - 125 psi
-----------------------	--------------

OPERATING TEMPERATURES

Minimum/Maximum	40° - 110° F
-----------------------	--------------

METER

Accuracy	± 5%
Flow Rate Range	1.5 - 125 gpm (5.7 - 473 lpm)
Volume Range	10 - 999,000 gallons (38 - 3,796.2 liters x1000)
Totalizer	1000 - 999,999,000 gallons

DIMENSIONS & WEIGHT

Distributor Pilot	
Valve Bodies with Female 2" NPT Inlet & Outlet.....	2.375" OD (2" NPS)
Valve Bodies with Female BSPT Inlet & Outlet	63mm OD
Drain Line	2" FPT or 2.5" Victaulic
Brine Line	1" MPT or 3/4" x 1" solvent weld
Adapters Available	1/2" or 5/8" OD Poly Tube
Mounting Base.....	4" - 8 UN, 6" Flange or Side Mount
Height From Top Of Tank.....	11" (280mm)
Shipping Weight With Meter	50 lbs (22.7 Kg)

ELECTRICAL SPECIFICATIONS

AC Adapter

	<u>U.S.</u>	<u>International</u>
Supply Voltage	120V AC.....	230V AC
Supply Frequency	60 Hz.....	50Hz
Output Voltage	24V AC.....	24V AC
Output Current	750 mA.....	750mA

TANK APPLICATIONS

Water Softener	18" - 63" Diameter
Water Filter (2)	18" - 48" Diameter

CYCLES OF OPERATION

Choose up to nine regeneration cycles, in any order, with a wide range of available values:

Cycle	Range of values
Backwash.....	1 - 95 minutes
Brine (draw)	1 - 180 minutes
Slow Rinse	1 - 95 minutes
Fast Rinse	1 - 95 minutes
Refill	0.1 - 99 minutes
Hold (service)	1 - 480 minutes

Options: Backwash Filter

Compatible with the following typical concentrations of regenerants or chemicals: Sodium chloride, potassium chloride, potassium permanganate, sodium bisulfite, chlorine and chloramines

1. See Distributor Pilot.

2. Filter tank size calculated @ 10 gpm of backwash per square foot of bed area